

56K Modem

Industrial 56K Dial-Up Modem

Imagine a reliable and economical 56K modem for masters, controllers and Autoscope dial-up datacomm applications.



Features

- Modem downloads at V.90/ K56flex speeds from a digital V.90 or K56flex server.
- Modem uploads at 33.6 Kbps (enhanced V.34).
- Standard RS-232 serial interface supporting DTE transfer speeds to 230.4 Kbps.
- Supports V.42 error correction with V.42bis or MNP Class 5 data compression.
- Supports industry-standard AT-style commands.
- Remote configuration, diagnostic tests, distinctive ring, 3-number storage for automatic dialing, and flash memory for firmware updates.

Description

The Industrial 56K Dial-Up Modem provides fully-integrated data communications over wide area networks using dial-up phone lines and the Internet.

The Industrial 56K Modem fully complies with Part 68 of the Federal Communications Commission (FCC) rules.

The Industrial 56K Dial-Up Modem is enclosed in a rugged metal housing. A terminal block/ connector provides power connection from a 24 VDC or 24 VAC source. Power can come from the supplied power puck or cabinet 24 VDC. A 9-pin serial connector and standard RJ11 phone jack provide the connections to the phone network from the controlling equipment.

Four red LED indicators show the status of communications (RD, TD, DCD, and DTR) and the power status of the modem.

Benefits

- Complete modem solution.
- 56Kbps performance.
- Full-featured datacom operation.
- Serial interface.
- Low power consumption.
- Small footprint.
- Shelf mount.
- Micro-controller technology for reliable long-life performance.



56K Modem

Industrial 56K Dial-Up Modem



Specifications

Data Rates: Client-to-Server

- Data communications support V.90 or K56flex for download speeds to 56 Kbps when connected to a fully digital V.90 or 56Kflex server, and upload speeds to 33.6 Kbps via enhanced V.34. Negotiates an enhanced V.34 (33.6 K), V.32bis (14.4 K), V.32 (9600), V.22bis (2400), or slower speed connection with non-V.90 modems.

Data Rates: Client-to-Client

- 33,600, 31,200, 28,800, 26,400, 24,000, 21,600, 19,200, 16,800, 14,400, 12,000, 9600, 7200, 4800, 2400, 1200, 0-300 bps.

Data Format

- Serial, binary, asynchronous.

Error Correction

- ITU-T V.42 (LAP-M or MNP3-4).

Data Compression

- ITU-T V.42bis (4:1 throughput), MNP 5 (2:1 throughput).

Speed Conversion

- Serial port data rates adjustable to 300, 1200, 2400, 4800, 9600, 19,200, 38,400, 57,600, 115,200, and 230,400 bps.

Flow Control

- XON/XOFF (software), RTS/CTS (hardware).

Command Buffer

- 40 characters.

Intelligent Features

- Fully AT command compatible; autodial, redial, repeat dial; pulse or tone dial; dial pauses; auto answer; adaptive line probing; automatic symbol and carrier frequency during startup, retrain, and rate renegotiation; DTMF detection; call status display, auto-parity and data rate selections; keyboard-controlled modem options; non-volatile memory; on-screen displays for modem option parameters; command lines of up to 40 characters each; help menus; remote configuration; DTR dialing.

Data Modulation

- FSK at 300 bps, PSK at 1200 bps, QAM at 2400, 4800, and 9600 bps (non-trellis), QAM with trellis-coded modulation (TCM) at 9600, 12,000, 14,400, 16,800, 19,200, 21,600, 24,000, 26,400, 28,800, 31,200, 33,600, and 56,000 bps.

Transmit Level

- -11 dBm (dial-up).

Receiver Sensitivity

- -43 dBm under worst-case conditions.

AGC Dynamic Range

- 43 dB.

Diagnostics

- Local analog loop, local digital loop, remote digital loop.

Interface

- Serial interface for EIA RS-232C/ITU-T V.24/V.28.
- Female 9-pin metal shell D subminiature connector with female jack screws.

Power

- 20 to 28 VAC/DC, not exceeding 5 watts (power puck provided).

Dimensions

- 1.6" x 4.2" x 6" (H x W x D).
- 41 mm x 107 mm x 152.4 mm (H x W x D).

Weight

- 1.0 lb.
- 0.45 kg.

Environmental

- -34°C to 74°C
- 0 to 95% relative humidity (non-condensing over the entire temperature range).

Approvals

- FCC Part 68 approved.
 - Industry Canada CSOs.
- Approvals provided in controlled configurations and must be reevaluated in end-user configurations.

Warranty

- Two-year warranty

Product Support

- Product support and training by a team of trained technical support specialists.

© 2003 Econolite Control Products, Inc. All rights reserved. Econolite Control Products, Inc. reserves the right to change or update these specifications at any time without prior notification.



3360 E. La Palma, Anaheim, CA 92806-2856
Tel: (714) 630-3700 • Fax: (714) 630-6349
E-mail: sales@econolite.com



#81-10257M-01

ECONOLITE
CONTROL PRODUCTS, INC.